

NOVO-4T



PRODUCT DESCRIPTION

Nomad Novo 4T Eco Scooter is a mineral motorcycle oil specially designed to meet today's 4-Stroke scooter specifications where a 20W40/50 viscosity grade and the JASO MB specification are required. JASO MB lubricant ensures optimal engine performance and fuel economy on all scooters without wet clutch.

APPLICATION

For older scooters without wet clutch and where JASO MB specification is required.

PROPERTIES

- Reduces oil consumption
- Provides Low Emission
- Outstanding detergent and anti-wear properties

PERFORMANCE LEVELS

Meets and exceeds:

API SG; JASO MB

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	NOMAD NOVO 4T ECO SCOOTER	
Viscosity Grade			20W40	20W50
Density @ 15°C	ASTM D1298	kg/l	0.880	0.880
Viscosity @ 100°C	ASTM D445	cSt	15.0	18.5
Viscosity @ 40°C	ASTM D445	cSt	122	160
Viscosity Index (min)	ASTM D2270	-	126	126
Pour Point	ASTM D97	°C	-25	-25
Flash Point	ASTM D92	°C	230	230
Total Base Number (TBN)	ASTM D2896	KOH/g	7.0	7.0

The values shown above are typical values at the date of publication. Nomad Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.nomad-lubricants.com