

NOVO-4T



PRODUCT DESCRIPTION

Nomad Novo 4T Eco is a mineral motorcycle oil designed primarily for on-road, four-cycle bikes. Reinforced with extreme pressure additives for gearbox protection and improve gears life time.

APPLICATION

Nomad Novo 4T Eco is designed primarily for on-road, four-cycle bikes. It also may be used in other types of on and off-road four-cycle motorcycles. Meets JASO MA1 specifications for optimal wet clutch performance. Also recommended for older big bore engines thumpers, twins, oil/air or liquid cooled engines

PROPERTIES

- Reduces oil consumption
- Allows smooth shifting
- Improves gears life time

PERFORMANCE LEVELS

Meets and exceeds:
API SG; JASO MA / MA1

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	NOMAD NOVO 4T ECO	
Viscosity Grade			20W40	20W50
Density @ 15°C	ASTM D1298	kg/l	0.880	0.880
Viscosity @ 100°C	ASTM D445	cSt	14.0	18.5
Viscosity @ 40°C	ASTM D445	cSt	100	160
Viscosity Index (min)	ASTM D2270	-	142	126
Pour Point	ASTM D97	°C	-30	-25
Flash Point	ASTM D92	°C	230	230
Total Base Number (TBN)	ASTM D2896	KOH/g	7.0	7.0

The values shown above are typical values at the date of publication. Nomad Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.nomad-lubricants.com