

NOVO-4T



PRODUCT DESCRIPTION

Nomad Novo 4T Endurance is a 100% synthetic 4-Stroke motorcycle racing lubricant. Ensures maximum power output of the engine without compromising the reliability and the wear. Meets JASO MA2 specifications for optimal wet clutch performance.

PROPERTIES

- Reduces engine internal friction
- Improves mechanical efficiency
- Very low volatility to reduce oil consumption
- Anti-oxidation, Anti-corrosion, Anti-foam properties

PERFORMANCE LEVELS

Meets and exceeds:

API SN / SM / SL / SJ / SH / SG; JASO MA / MA2

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	NOMAD NOVO 4T ENDURANCE
Viscosity Grade			10W60
Density @ 15°C	ASTM D1298	kg/l	0.860
Viscosity @ 100°C	ASTM D445	cSt	24.0
Viscosity @ 40°C	ASTM D445	cSt	156
Viscosity Index (min)	ASTM D2270	-	185
Pour Point	ASTM D97	°C	-33
Flash Point	ASTM D92	°C	236
Total Base Number (TBN)	ASTM D2896	KOH/g	8.0

The values shown above are typical values at the date of publication. Nomad Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.nomad-lubricants.com