

## DESCRIPTION

Nomad UTTO WB 101 is a super high-performance multifunctional transmission lubricant for construction machinery.

## PROPERTIES

This lubricant assures:

- highest pressure-absorption capability
- wear reduction
- noise reduction
- excellent viscosity/temperature properties
- excellent ageing resistance
- all sealing materials compatibility

## APPLICATIONS

Used in powered transmission and axle drives, especially for high-load hypoid gearings. Not to be used as engine oil.

Meets the requirements of: API GL 4, Case New Holland MAT-3525, M2C-134 A-D, FNHA-2- D.201.00, John Deere JDM-J20C, Massey-Ferguson M1143, M1145, Volvo WB 101, Transmission Oil 97303:015, ZF TE-ML 03E, 05F, 06D, 06K, 06M, 06N, 06R, 17E, 21F, Caterpillar TO-4

## TYPICAL PROPERTIES

<b>Nomad UTTO WB 101</b>		
<b>Typical Properties</b>	<b>SAE Grade</b>	<b>10W30</b>
<b>Test Parameters</b>	<b>Performance</b>	<b>GL-4</b>
	<b>ASTM Method</b>	<b>Typical Values</b>
<b>Density @ 15°C, kg/l</b>	ASTM D1298	0.870
<b>Viscosity @ 100°C, cSt</b>	ASTM D445	10.50
<b>Viscosity @ 40°C, cSt</b>	ASTM D445	69
<b>Viscosity Index</b>	ASTM D2270	135
<b>Flash Point, °C</b>	ASTM D92	230
<b>Pour Point , °C</b>	ASTM D97	-25