

STOU 15W30



PRODUCT DESCRIPTION

Nomad STOU 15W30 is a synthetic blend, extra high performance, multi-functional lubricant for most farm equipment applications

APPLICATION

Mixed diesel and gasoline-powered farm vehicles engines, transmissions and power systems requiring multifunctional fluid.

PROPERTIES

- Reduced sludge build-up and high temperature deposits
- Wear reduction
- Noise reduction
- TBN reserves
- Effective detergency/dispersancy
- Excellent ageing resistance
- Longer gasket and seal life

PERFORMANCE LEVELS

Meets and exceeds:

API SF/GL 4, Caterpillar TO-2; John Deere J27, J20CI Ford's Super Tractor Oil Universal (STOU) applications (M2C 159B); Massey-Ferguson CMS 1135 and CMS 1139; Allison C-4

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	Nomad STOU 15W30
Viscosity Grade			15W30
Density @ 15°C, kg/l	ASTM D1298	kg/l	0.885
Viscosity @ 100°C	ASTM D445	cSt	10.90
Viscosity @ 40°C	ASTM D445	cSt	65.6
Viscosity Index (min)	ASTM D2270	-	140
Flash Point, °C	ASTM D92	°C	220
Pour Point, °C	ASTM D97	°C	-30

The values shown above are typical values at the date of publication. Nomad Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.nomad-lubricants.com