

UTTO WB 102



PRODUCT DESCRIPTION

Nomad Agriculture Synthetic™ UTTO WB 102 is a super high-performance fully synthetic multifunctional transmission lubricant for construction machinery.

APPLICATION

Specially developed for very heavily loaded hydraulic and transmission systems of agricultural and earthmoving machines.

PROPERTIES

- Highest pressure-absorption capability
- Wear reduction
- Noise reduction
- Excellent viscosity/temperature properties
- Excellent ageing resistance
- All sealing materials compatibility

PERFORMANCE LEVELS

Meets and exceeds:

API GL-4; Allison C4; Case MS1207/MS1209; Cat TO-2; John Deere J20A; Massey; Ferguson M1141/M1143/M1145; Volvo WB 102; ZF TE-ML 03E

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	Nomad Agriculture Synthetic™ UTTO WB 102
Density @ 15°C, kg/l	ASTM D1298	kg/l	0.850
Viscosity @ 100°C	ASTM D445	cSt	12.1
Viscosity @ 40°C	ASTM D445	cSt	72.8
Viscosity Index (min)	ASTM D2270	-	164
Flash Point, °C	ASTM D92	°C	6,600 @ -30 °C
Pour Point, °C	ASTM D97	°C	358

The values shown above are typical values at the date of publication. Nomad Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.nomad-lubricants.com