

# CHAINSAW



## PRODUCT DESCRIPTION

**Nomad Milking Machine Oil 68** is a high-quality vacuum pump oil specially developed for use in milking machines. This oil is formulated from specially selected highly refined mineral oils. Milking machine reliability is of the utmost importance in dairy management.

## APPLICATION

The specifications and instructions from the assembly or equipment manufacturer must be followed.

Suitable for use in a variety of pumps designs operating in all temperatures and conditions. Also recommended for the lubrication of associated milk handling hydraulics and equipment.

## PROPERTIES

- Outstanding lubricating action
- Outstandingly adherent
- Excellent low temperature behavior
- Excellent viscosity/temperature properties

## PERFORMANCE LEVEL

Meets the requirements of: API SJ

## TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	Nomad Milking Machine Oil 68
Viscosity Grade			68
Density @ 15°C, kg/l	ASTM D1298	kg/l	0.87
Viscosity @ 100°C	ASTM D445	cSt	13
Viscosity @ 40°C	ASTM D445	cSt	100
Viscosity Index (min)	ASTM D2270	-	128
Flash Point, °C	ASTM D92	°C	220
Pour Point, °C	ASTM D97	°C	-35

The values shown above are typical values at the date of publication. Nomad Lubricants reserves the right to change these typical values without prior notice

## HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.nomad-lubricants.com](http://www.nomad-lubricants.com)