

CONING OIL



PRODUCT DESCRIPTION

Nomad Coning Oil Anti-splash coning oil based on paraffinic mineral oil, for raw and dyed polyamide or polyester yarns textured on any fast machine.

APPLICATION

Every industrial lubricant recommendation should be done after an expert consultation on the application in question. Only then the best lubricant can be selected.

Nomad Coning Oil can be used for raw and dyed polyamide or polyester yarns textured on any fast machine.

PROPERTIES

- Gets rid of oil splashes
- Suppresses dripping on yarn-guides
- Gives the yarns a good antistatic protection
- Reduces the friction coefficient yarn/metal and yarn/yarn
- Improves the regularity of oil pick up by the yarns
- Is easily removed in scours bath

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	Nomad CONING OIL
Density @ 15°C	-	kg/m ³	0.82-88
Flash Point, Cleveland	ASTM D92	°C	≥130
Viscosity @ 40°C	ASTM D445	mm ² /s	8-12
Visual Color		-	Colorless to slight yellow

The values shown above are typical values at the date of publication. Nomad Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.nomad-lubricants.com