

GEO 15W40



PRODUCT DESCRIPTION

Premium CNG/LNG oil formulated to deliver outstanding protection and long drain performance in a wide variety of compressed natural gas (CNG), liquefied natural gas (LNG) and liquefied petroleum gas (LPG) engine applications

APPLICATION

Formulated for diesel engines operating with higher pressures & temperatures and longer strokes.

Recommended for cylinder lubrication of the latest, highly rated low speed crosshead marine diesel engines operating on residual fuels with sulphur contents in excess of 1%.

PROPERTIES

- Alternative fuel performance:
- Great performance for medium and heavy duty vehicles using CNG, LNG or LPG.
- Excellent engine cleanliness
- Sludge control; and valve, or piston deposits in field trials and engine tests.
- Oil oxidation/nitration control

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	Nomad GEO SAE 15W40
Viscosity Grade	-	-	15W40
Density @ 15°C	ASTM D1298	kg/l	0.87
Viscosity @ 100°C	ASTM D445	cSt	15.8
Viscosity @ 40°C, cSt	ASTM D445	cSt	126
Viscosity Index (min)	ASTM D2270	-	132
Flash Point	ASTM D92	°C	230
BN	ASTM D2896	mg KOH/g	6
Pour Point , °C	ASTMD97	°C	-27

The values shown above are typical values at the date of publication. Nomad Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.nomad-lubricants.com