

PRODUCT DESCRIPTION

Nomad Power Steering Fluid has a sophisticated combination of high quality mineral based oils and viscosity index improve, anti-oxidant, anti-wear, detergent, and friction modifying additives.

APPLICATION

Used in automatic transmissions and manual transmissions, in torque converters and numerous power steering systems in accordance with the specifications of the manufacturer.

PROPERTIES

- Smooth transmission and perfect synchronization
- Longer retention of frictional characteristics under continual severe operating conditions
- Protection against deposit formation and evaporation losses at high operating temperatures
- Excellent low temperature operation, ensuring prompt circulation of fluid
- Good protection, against wear, resistance to rust, corrosion and foam
- Compatible with seal materials used in transmission units
- Lower maintenance costs, and improved operating profit

PERFORMANCE LEVELS

Meets and exceeds:

API SP and RC; API SN and RC; API SN Plus and RC; ILSAC GF-6B; GM dexos1™ Gen 2

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	Nomad Power Steering Fluid
Density @ 15°C	ASTM D1298	Kg/l	0.870
Viscosity @ 100°C	ASTM D445	cSt	8.0
Viscosity @ 40°C	ASTM D445	cSt	40
Viscosity Index	ASTM D2270	-	175
Pour Point	ASTM D97	°C	-36
Flash Point	ASTM D92	°C	200
Color	-	-	Blue

The values shown above are typical values at the date of publication. Nomad Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.nomad-lubricants.com