

UTTO 10W30



PRODUCT DESCRIPTION

Nomad UTTO 10W30 is a super high-performance fully synthetic multifunctional transmission lubricant for construction machinery.

APPLICATION

Used in powered transmission and axle drives, especially for high-load hypoid gearings. Not to be used as engine oil.

PROPERTIES

- Highest pressure-absorption capability
- Wear reduction
- Noise reduction
- Excellent viscosity/temperature properties
- Excellent ageing resistance
- All sealing materials compatibility

PERFORMANCE LEVELS

Meets and exceeds:

API GL 4, Case New Holland MAT-3525, M2C-134 A-D, FNHA-2- D.201.00, John Deere JDM-J20C, Massey-Ferguson M1143, M1145, Volvo WB 101, Transmission Oil 97303:015, ZF TE-ML 03E, 05F, 06D, 06K, 06M, 06N, 06R, 17E, 21F, Caterpillar TO-4

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	Nomad UTTO 10W30
Viscosity Grade			10W30
Density @ 15°C, kg/l	ASTM D1298	kg/l	0.870
Viscosity @ 100°C	ASTM D445	cSt	10.50
Viscosity @ 40°C	ASTM D445	cSt	69
Viscosity Index (min)	ASTM D2270	-	135
Flash Point, °C	ASTM D92	°C	230
Pour Point, °C	ASTM D97	°C	-25

The values shown above are typical values at the date of publication. Nomad Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.nomad-lubricants.com