

UTTO 15W30



PRODUCT DESCRIPTION

Nomad UTTO 15W30 is a super high-performance multifunctional transmission lubricant for construction machinery.

APPLICATION

Used in powered transmission and axle drives, especially for high-load hypoid gears. Not to be used as engine oil

PROPERTIES

- Highest pressure-absorption capability
- Wear reduction
- Noise reduction
- Excellent viscosity/temperature properties
- Excellent ageing resistance
- All sealing materials compatibility

PERFORMANCE LEVELS

Meets and exceeds:

API GL 4, Allison C-4; Ford ESN M2C 86B, C, Ford ESN M2C 134-D; Massey Ferguson M1135, M1141, M1143, M1145; NEW HOLL. FNHA-2-C-201.00; ZF TE-ML 03E, 05F, 06K, 17E, 21F quality

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	Nomad UTTO 15W30
Viscosity Grade			15W30
Density @ 15°C, kg/l	ASTM D1298	kg/l	0.885
Viscosity @ 100°C	ASTM D445	cSt	10.90
Viscosity @ 40°C	ASTM D445	cSt	65.6
Viscosity Index (min)	ASTM D2270	-	140
Flash Point, °C	ASTM D92	°C	220
Pour Point, °C	ASTM D97	°C	-30

The values shown above are typical values at the date of publication. Nomad Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.nomad-lubricants.com